Industrial 1000 / 800

Your introduction to large format heat pressing

Pneumatically operated, single drawer heat presses featuring a large pressing area of 109.5 × 80cm (Ind 1000) or 80 × 60cm (Ind 800), allowing you to press individual large items as well as multiple smaller products. Available with an optional, specifically designed robust stand the industrial range is perfect for all production environments.

Industrial 1000

Industrial 800

Machine Stand (optional)

Machine Features

- Heavy-duty build and reliability synonymous with Adkins.
- Modern digital touch screen.
- Pneumatic operation for consistent repeated pressure on every press cycle.
- Twin button control for pressing and manual release, ensuring operators hands are clear of the moving parts.
- Minimised operator fatigue allowing for continuous quality production.
- Emergency stop button to release the pressing bed and completely shut down the machine.
- Additional safety features including a layered heat plate cover, protective screw caps and pressing position safety lock.

Technical Specification	Industrial 1000	Industrial 800
Voltage:	220-240v AC (32 amp rate)	220-240v AC (32 amp rate)
Power Consumption:	5.8kw (average)	5kw (average)
Circuit Breaker:	32A	25A
Pressing Bed Size:	109.5(w) x 80(d) cm	80(w) x 60(d) cm
Machine Size (closed):	130(w) x 102(h) x 125(d) cm	85(w) x 102(h) x 125(d) cm
Machine depth Open:	173cm	173cm
Height With Stand:	156cm	156cm
Net Weight:	263kg	218kg
Package size:	138(w) x 126(h) x 153(d) cm	135(w) x 121(h) x 119(d) cm
Gross Weight:	371kg	314kg
Minimum Work Area:	190(w) x 120(h) x 240(d) cm	142(w) x 120(h) x 240(d) cm
Working Temperature:	0-230°C	0-230°C
Suggested Compressed Air Supply:	3.5 - 5.0 bar (51 - 65 Psi)	3.5 - 5.0 bar (51 - 65 Psi)

With decades of experience in producing high quality engineered heat transfer solutions, Adkins is a trusted brand worldwide.

adkinsmachines.com
sales@adkinsmachines.com
+44 1332 85 84 30

All products within the ADKINS range are labelled with CE marking and are manufactured and tested to comply with EU/EC safety regulations.